

SET-UP INSTRUCTIONS



Step 1: Remove your SpringHouse™ from the pack.



Step 2: Allow your SpringHouse™ to spring open.



Step 3: Unfold your SpringHouse™ into 2 panels.



Step 4: Unzip the easiest accessible doorway and screen. Grab the center steel band and lift up to separate the two sides of your SpringHouse™.



Step 5: Stand on the bottom corner of the skirting and lift your SpringHouse™ over your head. Push out on the center steel band (Shown in fig. D) and left up to separate the two sides of your SpringHouse™.



Step 6: Stand pm the bottom corner of the skirting and lift your SpringHouse™ over your head. Push out on the center steel band (Shown in fig. D) and left up to separate the two sides of your SpringHouse™.




Step 7: Secure your SpringHouse™ using the supplied stakes. Insert the stakes into the stake holes of the skirt at 45° angles.



Step 8: You must secure your SpringHouse™ using the High-wind tie-downs. Insert one end of the rope through the D-ring in the top corner, then through the anchor. Knot the rope around a stake and insert it in the ground at a 45° angle. Keep as much tension on the rope as possible. Repeat this step with all corner locations, as well as the D-rings on the peak ends and top center of the side walls.



Step 9: Begin with the X-shaped fiberpole. (See "I"). Insert the capped ends into the pockets above the doorways. Then completely assemble the fiberpole. (See "J").



Step 10: Beginning with **one** of the L-shaped fiberpoles, insert the capped end into the pocket in the center near the floor. (See "K"). Insert the uncapped end into the X-shaped piece. "See "L)". While assembling the L-shaped pole, keep it to one side. This will relieve some tension and allow for easier assembly. (See "Ka").



Step 11: Repeat Step 10 with the second L-shaped fiberpole. When the poles are completely assembled, move them to the center of the wall, and tie them to hold them in one place. See photo 11.

Step 12: The doorways of your SpringHouse™ can be secured open for ventilation. First unzip the top portion of the outer door. Roll it down and secure it with the straps.



Step 13: The screens can also be secured open. Unzip both the doorway and screen. Roll them together long ways. Secure with the straps.